

SPRINT 03

With transformer
in waterproof box
and encoder.



Technical specifications



Transformer power supply [Vac]	230 [+6% -10%] – 50 Hz
Absorbed power [W]	3
Max. Motor load [W]	70
Max. accessories load	24 Vdc 500 mA
Max. Blinker load	24 Vdc 15 W Max.
Operating ambient temperature	-20°C +55°C
Protective fuses	3
Function logics	Automatic/Automatic Step by step/Semi-automatic / Semi-automatic step by step/Condominium
Opening and closing time	Through self-learning during programming
Pause time	Through self-learning during programming
Thrust force	Four levels selectable on display
Selectable functions	Thrust force/Automatic closing/ OPEN A function/ Reversing at end-close/Condominium function/ Length of slowed down section/Speed during slow-down/ Working with or without limit-switches
Terminal board inputs	Power supply 22Vac/Batteries power supply /Encoder/Open total/ Open partial/Opening and closing safety devices/Stop/ Opening and closing limit-switches
Quick-fit connector	Genius 5 PIN receivers
Terminal board outputs	Accessories 24 Vdc power supply/ Motor 24Vdc power supply/ Blinker 24Vdc
Characteristics of optional Batteries	12V - 4 Ah/dimensions 90x70x108 mm